

STRATUS 23

V1

MAX. DIA. BUOY WATCH CIRCLE = 3.5 N.Miles

Position:

Water Line ~ 80 cm  
4 SBE 56 in from hull down beam block

Base with IMET Temp. Sensors at 1.0 m Depth, and Backup Xcote Transmitter

Interconnections to 70 meters coded with PVC tape and ductin on sensor

HARDWARE REQUIRED

(Includes approx. 20% Spare)

- (2) 1.25" Master Link
- (2) 1" Chain Shackles
- (1) 1" Anchor Shackles
- (2) 1" Weldless End Link
- (6) 7/8" Anchor Shackles
- (2) 7/8" Chain Shackles
- (114) 7/8" Weldless Links
- (158) 3/4" Chain Shackles
- (6) 3/4" Anchor Shackles
- (65) 5/8" Chain Shackles

HARDWARE DESIGNATION

- ④ U-Joint, 1" Chain Shackles, 1" EndLink, 7/8" Chain Shackles
- ③ 3/4" Chain Shackles, 7/8" EndLink, 3/4" Chain Shackles
- ② 3/4" Anchor Shackles, 7/8" EndLink, 3/4" Anchor Shackles
- ① 5/8" Chain Shackles, 7/8" EndLink, 5/8" Chain Shackles
- ① 5/8" Chain Shackles, 7/8" EndLink, 7/8" Anchor Shackles
- ① 1-1/4" Master Link, (1) 5/8" Ch Sh, (1) 7/8" End Link, (1) 7/8" Anc Sh

- 2.7 m Surflyn Foam MOBS Buoy with:
- (2) IMET-RIDDM Telemetry (1 RM young, 1 Senic)
  - (1) Stand Alone HRH (senior) (1) Locar HRH (2) Rotronics 1 w/ Barani Shie
  - (1) Stand Alone Kipp & Zonen SWR
  - (1) Valeport WXT 520 (1) SBE 39 Air Temp
  - (1) PAMEL P002/SBE/SAMI
  - (1) XEOS ROVER beacon (see 1x day)

