

STRATUS 21

V2

MAX. DIA. BUOY WATCH CIRCLE = 3.5 NMiles

Position: 19°38' S, 84° 55' W

Water Line ~ 60 cm
4 SBE 56 in (semi) full depth below deck

Base with IMET Temp. Sensors at 1.0 m Depth, and Backup Xeo Transmitter

Instruments to 70 meters coated with PVC tape and Ductin on sensors

- HARDWARE REQUIRED**
(Includes approx. 20% Spares)
- (2) 1.25" Master Link
 - (2) 1" Chain Shackles
 - (1) 1" Anchor Shackles
 - (2) 1" Weldless End Link
 - (0) 7/8" Anchor Shackles
 - (2) 7/8" Chain Shackles
 - (114) 7/8" Weldless Links
 - (156) 3/4" Chain Shackles
 - (6) 3/4" Anchor Shackles
 - (65) 5/8" Chain Shackles

- HARDWARE DESIGNATION**
- A U-Joint, 1" Chain Shackles, 1" EndLink, 7/8" Chain Shackles
 - B 3/4" Chain Shackles, 7/8" EndLink, 3/4" Chain Shackles
 - C 3/4" Anchor Shackles, 7/8" EndLink, 3/4" Anchor Shackles
 - D 5/8" Chain Shackles, 7/8" EndLink, 5/8" Chain Shackles
 - E 5/8" Chain Shackles, 7/8" EndLink, 7/8" Anchor Shackles
 - F 1-1/4" Master Link, (1) 5/8" Ch Sh, (1) 7/8" End Link, (1) 7/8" Anc Sh

- 2.7 m Surlyn Foam MOBS Buoy with:
- (2) IMET-IRIDIUM Telemetry (1 RM young, 1 Senio)
 - (1) Stand Alone HRH (seariser) (1) Laser HRH (2) Rotronics 1 w/ Barani Shie
 - (1) Stand Alone Hpps & Zonen SWR
 - (1) Voheler WKT 500, (1) SBE 39 Air Temp
 - (1) (1) PML PC02/SBE/SAMI
 - (1) XEOS ROVER beacon (see: 1x day)

